

The l3str-format package: formatting strings of characters

The L^AT_EX Project*

Released 2020-01-29

1 Format specifications

In this module, we introduce the notion of a string $\langle format \rangle$. The syntax follows that of Python's `format` built-in function. A $\langle format specification \rangle$ is a string of the form

$$\langle format specification \rangle = [[\langle fill \rangle]\langle alignment \rangle][\langle sign \rangle][\langle width \rangle][.\langle precision \rangle][\langle style \rangle]$$

where each [...] denotes an independent optional part.

- $\langle fill \rangle$ can be any character: it is assumed to be present whenever the second character of the $\langle format specification \rangle$ is a valid $\langle alignment \rangle$ character.
- $\langle alignment \rangle$ can be < (left alignment), > (right alignment), ^ (centering), or = (for numeric types only).
- $\langle sign \rangle$ is allowed for numeric types; it can be + (show a sign for positive and negative numbers), - (only put a sign for negative numbers), or a space (show a space or a -).
- $\langle width \rangle$ is the minimum number of characters of the result: if the result is naturally shorter than this $\langle width \rangle$, then it is padded with copies of the character $\langle fill \rangle$, with a position depending on the choice of $\langle alignment \rangle$. If the result is naturally longer, it is not truncated.
- $\langle precision \rangle$, whose presence is indicated by a period, can have different meanings depending on the type.
- $\langle style \rangle$ is one character, which controls how the given data should be formatted. The list of allowed $\langle styles \rangle$ depends on the type.

The choice of $\langle alignment \rangle =$ is only valid for numeric types: in this case the padding is inserted between the sign and the rest of the number.

*E-mail: latex-team@latex-project.org

2 Formatting various data-types

| | |
|------------------------------|--|
| <code>\tl_format:Nn</code> * | <code>\tl_format:nn</code> $\langle\textit{token list}\rangle$ $\langle\textit{format specification}\rangle$ |
| <code>\tl_format:cn</code> * | Converts the $\langle\textit{token list}\rangle$ to a string according to the $\langle\textit{format specification}\rangle$. The $\langle\textit{style}\rangle$, if present, must be s . If $\langle\textit{precision}\rangle$ is given, all characters of the string representation of the $\langle\textit{token list}\rangle$ beyond the first $\langle\textit{precision}\rangle$ characters are discarded. |
| <code>\tl_format:nn</code> * | |

| | |
|-------------------------------|--|
| <code>\seq_format:Nn</code> * | <code>\seq_format:Nn</code> $\langle\textit{sequence}\rangle$ $\langle\textit{format specification}\rangle$ |
| <code>\seq_format:cn</code> * | Converts each item in the $\langle\textit{sequence}\rangle$ to a string according to the $\langle\textit{format specification}\rangle$, and concatenates the results. |

| | |
|-------------------------------|---|
| <code>\int_format:nn</code> * | <code>\int_format:nn</code> $\langle\textit{intexpr}\rangle$ $\langle\textit{format specification}\rangle$ |
| | Evaluates the $\langle\textit{integer expression}\rangle$ and converts the result to a string according to the $\langle\textit{format specification}\rangle$. The $\langle\textit{precision}\rangle$ argument is not allowed. The $\langle\textit{style}\rangle$ can be b for binary output, d for decimal output (this is the default), o for octal output, X for hexadecimal output (using capital letters). |

| | |
|------------------------------|---|
| <code>\fp_format:nn</code> * | <code>\fp_format:nn</code> $\langle\textit{fpexpr}\rangle$ $\langle\textit{format specification}\rangle$ |
| | Evaluates the $\langle\textit{floating point expression}\rangle$ and converts the result to a string according to the $\langle\textit{format specification}\rangle$. The $\langle\textit{style}\rangle$ can be <ul style="list-style-type: none">• e for scientific notation, with one digit before and $\langle\textit{precision}\rangle$ digits after the decimal separator, and an integer exponent, following e;• f for a fixed point notation, with $\langle\textit{precision}\rangle$ digits after the decimal separator and no exponent;• g for a general format, which uses style f for numbers in the range $[10^{-4}, 10^{\langle\textit{precision}\rangle})$ and style e otherwise. When there is no $\langle\textit{style}\rangle$ specifier nor $\langle\textit{precision}\rangle$ the number is displayed without rounding. Otherwise the $\langle\textit{precision}\rangle$ defaults to 6. |

3 Possibilities, and things to do

- Provide a token list formatting $\langle\textit{style}\rangle$ which keeps the last $\langle\textit{precision}\rangle$ characters rather than the first $\langle\textit{precision}\rangle$.

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

F

| | |
|----------------------------------|----------|
| fp commands: | |
| <code>\fp_format:nn</code> | <u>2</u> |

| | I | | T |
|----------------|----------|---------------|----------|
| int commands: | | tl commands: | |
| \int_format:nn | 2 | \tl_format:Nn | 2 |
| | | \tl_format:nn | 2 |
| | S | | |
| seq commands: | | | |
| \seq_format:Nn | 2 | | |